



Low VF Bridge Rectifiers



Features

- Glass Passivated Chip Junction
- Low I_{RRM}
- Low VF
- High V_{RRM}

Benefits

- Case: GBJ
- Terminals: Solderable Per MIL-STD-750
- Reduced power loss and switching transistor
- Reduced snubbing


Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.


Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	GBJ1508L	Units
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	800	V
Maximum RMS voltage	V _{RMS}	560	V
Maximum DC Blocking Voltage	V _{DC}	800	V
Average Rectified Output Current	I _o	15.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	300	A
Maximum Forward Voltage at 7.5 A	V _F	0.95	V
Maximum DC Reverse Current @T _A =25 °C at Rated DC Blocking Voltage @T _A =125 °C	I _R	10 500	μA
Typical Junction Capacitance (Note1)	C _j	25	pF
Operating and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150	°C
Note: 1. Measured at 1MHz and applied reverse voltage of 4 VDC.			
2. Mounted on glass epoxy PC board with 4×1.5×1.5 (3.81×3.81 cm) copper pad			


RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Current Derating, Case



Typical Junction Capacitance




Typical Forward Voltage



Typical Reverse Current

PACKAGE OUTLINE DIMENSIONS

Note:unit In(mm)



Dimensions in inches and (millimeters)