




SCHOTTKY BARRIER RECTIFIER

**TO-220AB
MBR3060CT**



**ITO-220AB
MBR3060CTF**



Features

- Low forward voltage drop
- Low power losses
- High efficiency operation
- Lead Free Finish, RoHS Compliant

Applications

- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes

Maximum ratings and electrical characteristics (T_J = 25°C unless otherwise noted)

Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	60		V
Maximum average forward rectified current	per device	IF(AV)	30		A	
	per diode		15			
Peak forward surge current 8.3 ms single half sine- wave superimposed on rated load per diode			IFSM	210		A
Operating junction and storage temperature range			TJ, TSTG	-50 to +150		°C
Typical thermal resistance per leg	TO-220AB		RθJC	2		°C/W
	ITO-220AB			4		°C/W
Instantaneous forward voltage per diode			VF(1)	TYP.	MAX.	V
	IF=5A	TJ=25°C		0.50	0.57	
	IF=5A	TJ=125°C		0.43	-	
	IF=15A	TJ=25°C		0.73	0.80	
	IF=15A	TJ=125°C		0.68	-	
Instantaneous reverse current per diode at rated reverse voltage		TJ=25°C	IR(2)	5	50	uA
		TJ=125°C		5	-	mA

Notes:

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

(2) Pulse test: Pulse width ≤ 40 ms

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

FIG. 1 MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG. 3 TYPICAL FORWARD CHARACTERISTICS PER LEG






FIG. 4 TYPICAL REVERSE CHARACTERISTICS PER LEG




PACKAGE OUTLINE DIMENSIONS

Note:unit In(mm)


TO-220AB



ITO-220AB



Marking Information



- ① W : Company's trademark
- ② Product model : MBR3060CT or MBR3060CTF
- ③ PDC information :

Y X WW

WW:Week code(01 to 53)


X:Internal identification code

Y:Year code(ex:0=2020)

- ④  Double wafer



Packaging Information

1.Tube Dimensions



2. Inside Box

3. Outside Box



Packaging Information

NO	UNIT	Tube Dimensions			Inside Box			Outside Box		
Size	mm	A	B	C	L1	W1	H1	L2	W2	H2
		530	7	33	570	46	150	590	260	180
QTY	PCS	50PCS/Tube			Smallest package,1000PCS, 20 tube in total			5,000PCS/carton,5 boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm									