

Schottky Barrier Rectifier

DO-201AD
SR2100



Cathode  Anode

Features

- Low forward voltage drop
- Low power losses
- High efficiency operation
- Lead Free Finish, RoHS Compliant

Applications


- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes

Maximum ratings and electrical characteristics (T_J = 25°C unless otherwise noted)


Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	100		V
Maximum average forward rectified current			IF(AV)	2		A
Peak forward surge current 8.3 ms single half sine- wave superimposed on rated load per diode			IFSM	70		A
Operating junction and storage temperature range			T _J , T _{STG}	-50 to +150		°C
Typical thermal resistance per leg			R _{θJC}	20		°C/W
Instantaneous forward voltage per diode			VF	TYP.	MAX.	V
	IF=2A	T _J =25°C		0.76	0.79	
	IF=2A	T _J =125°C		0.72	-	
Instantaneous reverse current per diode at rated reverse voltage		T _J =25°C	IR	-	200	uA
		T _J =125°C		5	15	mA

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)


Current Derating, Case




Maximum Repetitive Surge Current



Typical Forward Voltage




Typical Reverse Current



PACKAGE OUTLINE DIMENSIONS


DO-201AD



DO-201AD mechanical data


UNIT		A	B	C	D
mm	max	26.5	9.5	1.3	5.3
	min	24.5	7.3	1.2	4.8
mil	max	1043.30	374.01	51.18	208.67
	min	946.57	287.40	47.24	188.97

Marking Information




①Product model : SR2100

②PDC information:




Packaging Information

1.Inside Box



2.Outside Box



Packaging Information

NO	UNIT	Inside Box			Outside Box		
Size	mm	L1	W1	H1	L2	W2	H2
		255	75	1115	415	280	320
QTY	PCS	Smallest package,1000PCS/carton			10,000PCS/carton,10 boxes in total		
Note	Tolerance	≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm					