


Schottky Barrier Rectifier

SS56L

SMB



Cathode  **Anode**

Features

- Low forward voltage drop
- Low power losses
- High efficiency operation
- Lead Free Finish, RoHS Compliant


Applications

- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes


Maximum ratings and electrical characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	60		V
Maximum average forward rectified current			IF(AV)	5		A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load			IFSM	120		A
Operating junction and storage temperature range			T _J , T _{STG}	-50 to +150		°C
Typical thermal resistance			R _{θJA}	50		°C/W
Instantaneous forward voltage			V _F	TYP.	MAX.	V
	IF=1A	T _J =25°C		0.45	0.50	
	IF=1A	T _J =125°C		0.38	-	
	IF=5A	T _J =25°C		0.63	0.68	
	IF=5A	T _J =125°C		0.58	-	
Instantaneous reverse current at rated reverse voltage		T _J =25°C	I _R	5	20	uA
		T _J =125°C		10	-	mA


RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Current Derating, Case



Maximum Repetitive Surge Current




Typical Forward Voltage



Typical Reverse Current

PACKAGE OUTLINE DIMENSIONS


SMB dimension definitions



SMB dimension values

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.40	0.006	0.016
D	3.30	3.95	0.130	0.156
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
L	0.75	1.50	0.030	0.059

Marking Information



① Product model : SS56

② PDC information:

Y X WW

WW: Week code(01 to 53)

X: Internal identification code

Y: Year code(ex:0=2020)